

MORBARK® BEEVER™ M20R FORESTRY

FEATURES


- » Infeed system consisting of one 20" (50.8 cm) diameter top compression feed roll, with a 26" (66.04 cm) wide x 9' (2.74 m) long live floor equipped with two strands of WDH-110 chain
- » Straight discharge chute includes hydraulically operated chip deflect with vertical and horizontal adjustment
- » Hydraulic front and dual rear stabilizers
- » 36" (91.44 cm) diameter x 33.375" (84.77 cm) wide drum with front pocket and six Babbitt-style knives with removable knife holders
- » Discharge clean out door on bottom
- » Steel guard enclosing valve bank and automatic feed system components
- » Spanish and English safety decals



A 6' (1.83 m) infeed bed with live WDH-110 chain drive

Advantage 3™ Drum creates more uniform chips

Remote Control



OTHER SPECIFICATIONS

- » Drum diameter: 36" (91.44 cm)
- » Drum width: 33.375" (84.77 cm)
- » Infeed Opening: 65" wide x 43" high (165 cm x 109.22 cm)
- » Throat Opening: 28" wide x 20" high (71.12 cm x 50.8 cm)
- » Frame: 2" x 10" tubular (5.08 cm x 25.4 cm)

OPTIONS

- » Forestry, rotating or top load discharge
- » Forestry Grate System
- » Custom paint and logo packages
- » Variable speed flow control
- » Tracks

SPECIFICATIONS

	US	METRIC
Chipping Capacity	20"	50.8 cm
Length	26'8"	8.12 m
Height	11'	3.35 m
Width	8'	2.44 m
Gross Weight (approx.)	18,000 lb	8,165 kg
Suspension (Torsion)	20,000 lb	9,071 kg
Tandem Axle	20,000 lb (9,071 kg) torsion	
Engine	CAT	
Horsepower	350 to 415 HP	260 to 309 kW
Fuel Capacity (tank)	65 gallons	246 litres
Hydraulic Oil	44 gallons	166 litres
Tires	(4) 235/75x17.5	
Towing Arrangement	Pintle Hitch Tongue with Skidder Plates	



MORBARK®

www.morbark.com

800.831.0042

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS

11/20/18