

BOXER®

A MORBARK® COMPANY

The **700HDX** features a unique hydraulically expandable undercarriage — from 35" (89 cm) to 43.5" (111 cm) — allowing the operator to retract the undercarriage for passages as narrow as 36" (91 cm) wide then expand for increased stability while in operation by simply pulling or pushing a control lever. With a 24.8-HP (18.5-kW) diesel engine and 11.3/8.7 gpm (43/33 L/min) high/low hydraulic auxiliary flow, the 700HDX provides all the power you need for tough jobs. The 700HDX boasts a variety of new features, including a redesigned platform with added creature comforts, hydrostatic drive, piloted joystick controls, rubber-isolated engine and hydraulic components, tightened boom tolerances and a whole lot more!



MADE FOR **MORE** TO KEEP PACE WITH **YOU**

700HDX

MINI SKID STEER

FEATURES AND BENEFITS

- 24.8-HP (18.5 kW) Kubota D1105 Diesel Engine
- 2,020 lb (915 kg) tip capacity
- 707 lb (320 kg) operation capacity (35% tip load)
- Stand-on platform with generous hip padding and added creature comforts for operator safety and comfort
- Dual hydrostatic operating system
- Piloted joystick controls with rocker-activated auxiliaries
- 2-button pressure relief block
- 2.5" (64 mm) bore-welded tilt cylinder and two 2" (50 mm) bore-welded lift cylinders
- 0.25" (6 mm) thick laser-cut base sides and 0.75" (19 mm) thick boom arms
- Well-balanced and stable, with excellent ground speed
- Universal compact utility loader mounting plate and quick-attach system to quickly and easily switch between any standard attachment



S STEVENS
GROUP

www.stevensgroup.co.nz
sales@stevensgroup.co.nz
09 275 0443



MORBARK®

SPECIFICATION	US	METRIC
Engine Type		Kubota
Cooling System		Liquid
HP/kW	24.8 HP	18.5 kW
Fuel Type		Diesel
Fuel Capacity	9 Gallons	34 Litres
Hydraulic Capacity	24 Gallons	91 Litres
System Flow (Total)	27.1 GPM	103 L/min
Hydraulic Flow Aux (Hi/Lo)	11.3/8.7 GPM	43/33 L/min
Hydraulic Flow (Drive)	7.1 GPM	27 L/min
System Pressure	3000 PSI	20684 kPa
Engine Warranty		2 years
Product Warranty		1 year
Track Gauge	33.75"	857 mm
Track Width	9"	230 mm
Weight (No Attachment)	2880 lb	1306 kg
Length (No Attachment)	77"	1956 mm
Length (w/Bucket)	96"	2438 mm
Width (Fully Retracted)	34.5"	876 mm
Width (Fully Extended)	43.5"	1105 mm
Height (Boom Lowered)	54"	1372 mm
Height (Boom Raised)	98"	2489 mm
Hinge Pin Height	77"	1956 mm
Dump Height	60"	1524 mm
Dump Angle		37 Degrees
Reach	34"	864 mm
Tip Capacity	2020 lb	915 kg
Operating Capacity, 35% of tip load	707 lb	320 kg
Ground Clearance	5"	127 mm
Ground Speed	4.5 MPH	7.2 km/h
Ground Pressure	4.21 PSI	29.7 kPa

Updated 3/17/2020