

With its power and easily transportable design, the compact and economical **Eeger Beever 1215 Brush Chipper** is everything you need and nothing that you don't. The ideal machine for utility line clearing, residential tree care, rental yards, and municipalities.

Remove the anxiety of engaging the chipper drum, damaged drive belts, and burned clutch discs and elevate your operating experience with the exclusive Morbark ZeroClutch™ available now on select engine packages. Simply start, throttle the machine to full RPM's and engage the feed control bar. The Morbark ZeroClutch features an integrated drum speed sensor that monitors the drum speed and will allow the clutch to engage if material is lodged between the feed wheel and drum, or the discharge chute is plugged. Ask your Morbark dealer or representative about the Morbark ZeroClutch today.

FEATURES AND BENEFITS

- Full-length channel frame extends beneath the infeed for increased structural support.
- Extendable drawbar with two (2) pinned extensions allows greater flexibility when mating to tow vehicle
- Powerful TorqMax[™] single (top) feed wheel compression system amplifies material pulling power
- Dual-sided air impeller system increases air velocity to aid in discharging fibrous, light, and leafy material

MORBARK[®]

 Large infeed perimeter opening allows ample room to fee material, reducing saw and trim labor



sales@stevensgroup.co.nz

09 275 0443



1215 BRUSH CHIPPER SPECIFICATIONS

Specifications may vary with equipment options

Updated 10/12/20

GENERAL	US		METRIC
Height	9'		2.74 m
Width	6'2"		1.9 m
Length (operating)	15'6"		4.72 m
Gross weight (approximate)	5,200 lb		2,359 kg
Suspension	7,000 lb Torsion		3,175 kg Torsion
Infeed opening (height x width)	31" x 60"		78.7 x 152.4 cm
Throat opening (height x width)	12" x 15"		30.5 x 38.1 cm
Drum (width x diameter)	14.5" x 21.4"		36.8 x 54.4 cm
Engine		CAT, Isuzu or PSI	
Horsepower	48–75 HP		35.8–55.9 kW
Fuel capacity	24.5 gallons		92.7 L
Hydraulic capacity	17 gallons		64.4 L
Frame	8.2 lb, 6" channel		3.7 kg, 15.2 cm channel
Tires		(2) 235/80Rx16	
Hitch	2.5" Pintle		6.4 cm Pintle

EQUIPMENT HIGHLIGHTS

- Choice of gasoline or diesel engine packages
- Staggered pocket drum with two (2) dual-edged chipper knives
- Dual-sided air impeller system to increase chip throwing velocity
- Reversing automatic feed system
- Four (4) position feed control bar with dual safety pull cables located within the infeed
- 360° manual swivel discharge with multiple locking positions
- Pinned chipper hood with integrated hood safety plug
- Integrated tube and jack support pad to utilize from the drawbar jack to raise the feed wheel
- Standard fuel tank sight gauge, drain plug, and shut-off
- Standard hydraulic tank clean-out cover, shut-off valve, and magnetic drain plug
- Interstate Battery

OPTIONS INCLUDE

- Bottom Bump Bar
- Cone Holder
- Chocks/Chock Holder
- Folding Infeed Tray
- Spare Tire and Mount
- Strobe Light
- Pusher Paddle
- Infeed Curtain
- Rear Jacks



