



MORBARK

Featuring a highly configurable platform, the **Eger Beaver 2131 Brush Chipper** is available in single axle, tandem axle and track configurations - making it one of the most versatile chippers in Morbark's stable of tree care equipment. With scalable horsepower, extra wide infeed opening, large diameter drum and Variable Force™ hydraulic down pressure system, the Eger Beaver 2131 Chipper is a well-equipped combination of power, performance and capacity - making this the ideal unit for residential tree services, lot clearing, vegetation management, maintenance contractors, municipalities and more.



MADE FOR MORE TO KEEP PACE WITH YOU



EGER BEEVER

2131

BRUSH CHIPPER

FEATURES AND BENEFITS

- Highly configurable platform with choice of gas or diesel engine packages and single or tandem axle configurations.
- Extra wide feed wheels make feeding simple, especially when feeding with an auxiliary loader unit
- Powerful TorqMax™ top feed wheel drive system amplifies pulling power for the most demanding applications
- Direct drive bottom feed wheel with clean-out door is speed matched to the top feed wheel to provide continuous material flow
- Large diameter chipping drum with staggered knife pockets maintains chipping power while providing consistent chip quality
- Four (4) dual-edged chipper knives with replaceable knife holders allows ease of chipper drum maintenance and allows the drum to be rebuilt versus replaced, reducing expenses



www.stevensgroup.co.nz
sales@stevensgroup.co.nz
09 275 0443



MORBARK



EEGER BEEVER

2131 BRUSH CHIPPER SPECIFICATIONS

Specifications may vary with equipment options

Updated 10/12/20

	GENERAL	US	METRIC
GENERAL	Infeed opening (height x width)	36" x 59"	91.4 cm x 149.9 cm
	Throat opening (height x width)	20.5" x 31"	52.1 x 78.7 cm
	Drum (width x diameter)	23.5" x 37.4"	59.7 x 94.9 cm
	Engine	CAT, Ford, GM, Isuzu, John Deere or Perkins	
	Horsepower	140–275 HP	104.4–205 kW
	Fuel capacity	60 gallons	227.1 L
	Hydraulic capacity	41 gallons	155.2 L
	Frame	2" x 6" Tube Steel	5.1 x 15.2 cm Tube Steel
	Tires	235/75Rx17.5	
	Hitch	2.5" Pintle	6.4 cm Pintle
SINGLE AXLE	Height	9'	2.74 m
	Width	7'8"	2.31 m
	Length	21'8"	6.6 m
	Gross weight (Approximate)	11,100–12,700 lb	5,035–5,761 kg
	Suspension	(1) 12,000 lb Torsion Axle	(1) 5,443.1 kg Torsion Axle
TANDEM AXLE	Height	8'11"	2.72 m
	Width	8'	2.44 m
	Length	21'8"	6.6 m
	Gross weight (Approximate)	12,900 lb–15,000 lb	5,851–6,803.9 kg
	Suspension	(2) 8,000 lb Torsion Axles	(2) 3,628.7 kg Torsion Axles

EQUIPMENT HIGHLIGHTS

- Choice of gasoline, or diesel engine packages
- Choice of single, or tandem axles
- Staggered knife pocket drum with four dual-edged chipper knives and replaceable knife holders
- Dual sided air-impeller system increases chip velocity, aiding in discharging wet, leafy and fibrous material
- Feed wheels equipped with serrated teeth and knife bar combination for continuous material flow
- Reversing automatic feed system stops and momentarily backs away material for increased feeding efficiency and quicker engine recovery
- Standard fuel sight gauge, drain plug and shut-off valve.
- Standard hydraulic reservoir clean-out/inspection cover, magnetic drain plug and sight gauge
- Stacked tubular steel frame rails fully supports the entire chassis and increases structural integrity

OPTIONS INCLUDE

- ChipSafe® Operator Safety Shield
- Winch Package
- Hydraulic Swivel Discharge
- Hydraulic front and rear stabilizers
- Bottom Bump Bar
- Chocks and chock holders
- Traffic cone holder



www.stevensgroup.co.nz
 sales@stevensgroup.co.nz
 09 275 0443



MORBARK®