



MORBARK

When the job takes you off-road, the **Eeger Beever 2230 Track Brush Chipper** maintains the same features of the trailer mounted version with the added flexibility of a Caterpillar 312B undercarriage. The low ground pressure track undercarriage provides the versatility to take the chipper to the material, allowing greater chipping flexibility in hard to reach, traverse and navigate terrain.

The ideal unit for off-road applications, fire mitigation, utility line clearing and land clearing, highway clean-up, and more.



MADE FOR MORE TO KEEP PACE WITH YOU



**EEGER
BEEVER**

2230

**TRACK
BRUSH
CHIPPER**

FEATURES AND BENEFITS

- Reliable Caterpillar 312B undercarriage with 500 mm rubber tracks, two-speed travel and low ground pressure allows the operator to take the machine to the material, reducing logistics and creating a more efficient jobsite.
- 5' (1.5 m) live infeed deck with two rows of flighted infeed chain allow ease of material feeding - ensuring continuous material flow
- Cut-away infeed design provides unimpeded material flow - reducing the need for additional processing steps
- Powerful TorqMax™ top feed wheel drive system amplifies pulling power for the most demanding applications
- Variable Force™ Hydraulic Down Pressure System provides constant material crushing power -eliminating down pressure springs
- 360° Hydraulic Swivel Discharge aids in controlled discharge of processed material
- Wireless remote control operation with tethered back-up system allows automated control of the chipper to increase visibility, mobility and jobsite efficiency



**STEVENS
GROUP**

www.stevensgroup.co.nz
sales@stevensgroup.co.nz
09 275 0443



MORBARK®



EEGER BEEVER

2230 TRACK CHIPPER SPECIFICATIONS

Specifications may vary with equipment options

Updated 10/12/20

GENERAL	US	METRIC
Height	10'10"	3.30 m
Width	8'6"	2.59 m
Length	22'7"	6.88 m
Gross weight (approximate)	24,720 lb	11,213 kg
Infeed opening (height x width)	39" x 65"	109.2 x 165.1 cm
Throat opening (height x width)	22" x 30"	55.9 x 76.2 cm
Drum (width x diameter)	28.5" x 37.4"	72.4 x 94.9 cm
Engine	CAT	
Horsepower	415 HP	309.5 kW
Fuel capacity	65 gallons	246 L
Hydraulic capacity	45 gallons	170.3 L
Frame	2" x 8" Tube Steel	5.1 x 20.3 cm Tube Steel
Track	Caterpillar 312B Undercarriage with 500 mm steel tracks	
Ground Pressure	4.24 PSI	33.4 kPa
Ground Speed (Low/High)	80 FPM/120 FPM	24.4 m/min/36.6 m/min
Front Mounted Hitch	2.5" Pintle	6.4 cm Pintle

EQUIPMENT HIGHLIGHTS

- Staggered knife pocket drum with six dual-edged knives and replaceable knife holders
- Chambered air impeller system increases chip velocity and aids in discharging wet, leafy and fibrous material
- Pegged top feed wheel with serrated teeth filler bars ensures continuous material flow
- Reversing automatic feed system stops and momentarily backs away material for increased feeding efficiency
- Standard fuel sight gauge, drain plug and shut-off valve
- Standard hydraulic reservoir clean-out/inspection cover, magnetic drain plug and sight gauge
- Fully extended tubular steel frame fully supports the entire chassis

OPTIONS INCLUDE

- ChipSafe™ Operator Safety Shield
- Caterpillar 312B steel track undercarriage
- Winch Package
- Bottom Bump Bar
- Variable Speed Flow Control
- 5# (2.27 kg) ABC Fire Extinguisher with mount



www.stevensgroup.co.nz
sales@stevensgroup.co.nz
09 275 0443



MORBARK®