



# RAYCO

A MORBARK® COMPANY



MADE FOR **MORE** TO KEEP PACE WITH **YOU**

# C275R FORESTRY MULCHER

## FEATURES AND BENEFITS

- Powerful 275-hp CAT diesel engine
- Rayco-exclusive elevated cooling system
- Reversing fan for upper coolers
- Heavy-duty undercarriage
- Remote track tension system with tension monitor
- 2-speed ground travel
- Hydraulic rear winch
- Hydraulic cab tilt
- Certified ROPS/FOPS/OPS Cab
- Rear view camera
- Heated seat w/air-ride suspension
- Roof-top escape hatch
- High-output LED work lights
- Available with Predator mulcher head or Hydra-Stumper cutter head.



102 gpm cutter system provides hydraulic power to 7-foot Predator mulcher head.



40-inch diameter Hydra-Stumper cutter head



[www.stevensgroup.co.nz](http://www.stevensgroup.co.nz)  
[sales@stevensgroup.co.nz](mailto:sales@stevensgroup.co.nz)  
09 275 0443



**MORBARK®**

**RAYCO**

A MORBARK® COMPANY

**C275 FORESTRY MULCHER & HYDRRA-STUMPER  
SPECIFICATIONS**

| General                | US   | Metric              |
|------------------------|--|---------------------|
| Weight of Carrier Only | 23,165 lb  | 10,507 kg           |
| Length of Carrier Only | 185"   |                     |
| Height                 | 120"   | 304 cm              |
| Width                  | 96.25"   | 244 cm              |
| Engine                 | 275-hp CAT   | 205 kW              |
| Fuel Type              |  | Diesel              |
| Fuel Capacity          | 95 gallon  | 359 L               |
| Hydraulic Tank         | 25 gallon  | 94 L                |
| Track Width            | Standard: Single Grouser, Steel - 24" (600 mm)<br>Optional: Single Grouser, Steel - 20" (500 mm) or 28" (700 mm) |                     |
| High Flow Hydrostatic  | 102 gpm • 6,090 psi  | 386 L/min • 420 bar |
| Travel Speed High      | 3.6 mph  | 6 km/h              |
| Travel Speed Low       | 1.8 mph  | 3 km/h              |
| Cab Certifications     | ROPS ISO 8082-1 • FOPS ISO 8083 • OPS ISO 8084/J1356   |                     |

**PREDATOR MULCHER HEAD**

| Mulcher Head Model            | FM275-7R          |           |
|-------------------------------|-------------------|-----------|
| Weight                        | 4,295 lb          | 1,948 kg  |
| Weight with Carrier and Winch | 27,460 lb         | 12,455 kg |
| Length with Carrier and Winch | 254"              | 645 cm    |
| Overall Width                 | 93.125"           | 236 cm    |
| Rotor Diameter                | 20"               | 50 cm     |
| Rotor Speed                   |                   | 2050 RPM  |
| Ground Pressure               | 5.03 PSI          | 34.7 kPa  |
| Cutting Width                 | 77.5"             | 196 cm    |
| Max Mowing Height             | 46"               | 118 cm    |
| Cutter Teeth                  | 42 Carbide Tipped |           |

**HYDRRA-STUMPER CUTTER HEAD**

| Hydra-Stumper Model           | CB275HS   |                     |
|-------------------------------|-----------|---------------------|
| Weight                        | 4,400 lb  | 1,995 kg            |
| Weight with Carrier and Winch | 27,560 lb |                     |
| Length with Carrier and Winch | 276"      |                     |
| Wheel Diameter                | 40"       | 102 cm              |
| Wheel Thickness               | 3"        | 7.6 cm              |
| Drive Belt                    |           | Gates Polychain® GT |
| Cutter Wheel RPM              |           | 650 RPM             |
| Ground Pressure               | 5.05 PSI  | 34.83 kPa           |
| Cutter Teeth                  |           | 36 Monster Tooth™   |
| Below Ground Cutting Level    | 40"       | 102 cm              |
| Above Ground Cutting Level    | 59"       | 150 cm              |
| Cutting Width                 | 108"      | 274 cm              |



www.stevensgroup.co.nz  
sales@stevensgroup.co.nz  
09 275 0443

**MORBARK®**

07-2021