

MADE FOR MORE TO KEEP PACE WITH YOU

## SUPER Jr

## **FEATURES AND BENEFITS**

- Slewing ring pivot design increases cutting width
- Full cutting depth across entire width of cut
- Lower center of gravity
- Wide tires for enhanced traction and flotation
- Swing-out operator station for better visibility
- Controls swing in line for travel through gates
- · Gasoline engines with heavy duty air filter
- 27-hp Vanguard engine
- Centrifugal precleaner
- Optional hydraulic backfill blade
- Optional dual rear wheels & Command Cut









General	US	Metric
Weight	1,770 lb	803 kg
Length	114"	290 cm
Height	52"	132 cm
Width	35"	89 cm
Width with		
Dual Wheels (Maximum)	52.5"	133 cm
Ground Drive	Single Speed	
Tires	18 x 8.5-10 R4 4-ply	
Backfill Blade	Optional	
Engine	27-hp Vanguard	20-kW Vanguard
Fuel Type	Gasoline	Petrol
Maximum Rated Torque	27 ft-lb at 2500 RPM	36.6 Nm at 2500 RPM
Fuel Tank Capacity	5 gallon	18.9 L
Electrical System	12 volts/15 AMP alternator	
Oil Tank Capacity	2 gallon	7.6 L
Cutting Wheel Diameter	17.25"	43.8 cm
Cutting Wheel Thickness	1"	2.5 cm
Cutting Wheel Bearings	1.5" Pillow Block Type	3.81 cm Pillow Block Type
Super Tooth®	18 Total	
Clutch	Electromagnetic with "Quick Stop" Brake System	
Cutting Depth	12"	30 cm
Cutting Height	24.5"	62.2 cm
Cutting Width	51"	130 cm



Equipped with 18 Rayco Super Teeth®.



51-inch cutting width for full cutting depth across entire width of cut.



Available with custom trailer (TRG).



