









VX4° DECK Engineered to move more grass at high-speeds while maintaining cut-quality



I3M SUSPENSION SEAT High-back seat with adjustable armrests and 3-inch travel range



PATENTED BELT DRIVE SYSTEM Helps provide long-life to the machine

	DIESEL Z
ENGINE	
ENGINE	Delite
Manufacturer HP	Perkins 25HP
Displacement	1130cc
Cooling	Liquid cooled, direct-drive, mechanical cooling fan
Air Cleaner	Heavy duty cannister
Engine Warranty	3 year
DRIVE SYSTEM	
Туре	Dualhydrostatic
Pumps	Tandem 21cc Hydro-Gear [®] pumps
Wheel Motors	Parker TG0335
Hydraulic Lines	Stainless steel Parker Seal-Lok™ technology
Hydraulic Cooling	Oil cooler with 8" fan
Reservoir Capacity	4.9 Litres
Speed	Up to 18 kph
Parking brakes	Patented automatic
DECKS	
Cutting width	Side and rear discharge: 60", 72"
Cutting height	1" - 5.5"
Deck lift	Foot operated
Depth	5.5"
Blades	3
Blade Length	60" deck: 3-20.5" x 3.0" x 0.203" 72" deck: 3-24.5" x 3.0" x 0.250"
Blade Tip Speed	60": 18,200 72": 18,800
Spindles	Ductile cast iron with steel shafts and sealed ball bearings
Drive	Electric PTO clutch
Construction	7 ga. welded steel
Spindle Mounts	Reinforced 7 ga. stamped disc
Impact/Trim Areas	Front of deck: 11 ga. formed bump bar Side of deck: 1.5" x 0.375" steel bar
CONSTRUCTION	
Frame	1.5" x 3.0" x 0.188" steel tubing
Front Caster Wheels	Mounted tapered greasable bearings & debris cap
Front Caster Forks	Fabricated 1/2" steel
GENERAL	
Seat	I3M suspension seat
Fuel Capacity	54.5 Litres
Cupholder	Yes
Front Tyre	13 x 6.5 - 6
Drive Tyre	24 x 12 -12
DIMENSIONS	
Weight	60" deck: 751kg 72" deck: 776kg 60" deck RD: 801kg 72" deck RD: 824kg
Height w/rops	1.75m
Height w/rops folded	1.30m
Length	60", 60" RD deck: 2.20m 72", 72" RD deck: 2.30m
Width w/Chute	60", 60" RD deck: 1.68m 72", 72" RD deck: 1.98m
Tyre width	1.42m
Trim Side	60", 60" RD deck: 0.12m 72", 72" RD deck: 0.29m
ACCESSORIES	
	Mulch kit, FlexForks°, semi pneumatic front tyres, steering lever extension kit, electric deck lift, hitch kit
PRODUCTIVITY*	
Acres per hour	60": 5.57 72": 6.68
VISIT HUSTLERMOWE and try our compare	

Specifications are subject to change without notice * Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain

V1 11/2020