











RAPTOR AVAILABLE DECK SIZES

42"- 54"

T





Welded Steel Deck

NEW!

Wider Stance

the operator

Additional operator

platform width provides

more room and comfort for

11 ga. welded fabricated steel deck adds durability & extends mower's life

Premium Residential Frame

Continuous one-piece 1 1/2 inch by 3 inch welded tubular frame not seen on any other residential mower. #1 in Class



Foot Operated Deck Lift Easily adjust the deck height between 1.5" - 4.5" with less effort than handoperated levers found on other brands

SmoothTrak[™] Steering

Precision control to help trim and maneuver easily around obstacles. You will fully understand SmoothTrak[™] steering when you drive ours

NEW!



Premium Seat Provides a comfortable ride with armrests and added airflow to the back

Premium Power V-Twin Kawasaki® engine is the highest rated residential engine available **NEW!**

Exclusive BigBite[™] **Rear Tyres** We worked directly with the tyre manufactuer on this design. You will not find them anywhere else.

Easy to Service Flip-up seat pan, removable floor pan, vented pulley covers











- Mulch kit
- Grass bagger (non-powered 5.4 bushels)
- Steering lever extension kit
- ▶ FlexForks[™]

UPGRADES FOUND ON THE RAPTOR XD



- Higher-back seat and added padding
- Larger Transmissions Hydro-Gear[®] ZT2800
- S Larger 20" BigBite[™] drive tyres
- Heavier deck
- Oeck travel latch









RAPTOR X

RAPTOR XD

ENGINE		
Manufacturer	Kawasak	i® FR series
HP	42" deck: 21HP - FR651 54" deck: 23HP - FR691 (Per SAE J1995)	42" & 48" deck: 21.5HP - FR651 54" deck: 23HP - FR691 (Per SAE J1995)
Displacement	42" deck: 603 cc 54" deck: 726cc	42" & 48" deck: 603 cc 54" deck: 726cc
Cooling	Air cooled	
Engine Warranty	3 year	
DRIVE SYSTEM		
Туре	Dual hydrostatic	
Transmission	Hydro-Gear® ZT2200	Hydro-Gear® ZT2800
Speed	Up to 11kph	Up to 12kph
Parking Brakes DECKS	Patente	d automatic
Cutting Width	Side discharge: 42", 54"	Side discharge: 42", 48", 54"
Cutting Height	-	5" - 4.5"
Deck Lift	Foot operated	
Depth	4.5"	
Blades	42" deck: 2 54" deck: 3	42" deck: 2 48",54" deck: 3
Blade Length	42" deck: 20.50" 54" deck: 18.50"	42" deck: 2 46,54 deck: 3
Blade Tip Speed	42" deck: 18,000 54" deck: 18,600	42" deck: 18,400 48" deck: 18,500 54" deck: 18,800
Spindles	Aluminium with 1" shafts and double lip sealed ball bearings	
Drive	Electric PTO Clutch	
Construction	Fabricated 11 ga. steel	
Spindle Mounts	Reinforced 7 ga. steel	
Impact/Trim Areas	1/4" x 1" steel bar	3/8" x 1" steel bar
CONSTRUCTION		
Frame	1.5" x 3" steel tubing	
Front Axle	Fabricated with sealed ball bearings	
Front Caster Wheels	Sealed ball bearings	
Front Caster Forks	Fabricated 1/4" steel	Fabricated 3/8" steel
GENERAL		
Seat	Premium bolstered seat with built-in lumbar support	
Fuel Capacity	11.4 Litres	
Cupholder	Yes	
Front Tyre	42": 11 x 5 54": 11 x 6	42": 13 x 5 48", 54": 13 x 6.5
Drive Tyre	42": 18 x 8.50 - 8 BigBite" 54": 18 x 10.50 - 8 BigBite"	42" & 48": 20 x 8-10 BigBite" 54": 20 x 12-12 BigBite"
DIMENSIONS		
Weight	42" deck: 244kg 54" deck: 256kg	42" deck: 279kg
Height	1.02m	1.11m
Length	42" deck: 1.75m 54" deck: 1.79m	42" & 48" deck: 1.76m 54" deck: 1.80
Width w/Chute	42" deck: 1.16m 54" deck: 1.49m	42" deck: 1.16m 48" deck: 1.33m 54" deck: 1.49m
Tyre width	42" deck: 1.09m 54" deck: 1.18m	42" & 48" deck: 1.06m 54" deck: 1.23m
Trim Side	42" deck: 0.01m 54" deck: 0.14m	42" deck: 0.03m 48" deck: 0.11m 54" deck: 0.08m
PRODUCTIVITY*	72 UCOR. 0.0 mill 04 UCOR. 0.14m	42 ueck. 0.03111 40 ueck. 0.11111 34 ueck. 0.08111
	10" doole 0.00 E1" doole 0.01	10" dool 0 EA 10" dool 0 01 EA" dool 0 07
Acres per hour	42" deck: 2.38 54" deck: 3.01	42" deck: 2.54 48" deck: 2.91 54" deck: 3.27



VISIT HUSTLERMOWERS.CO.NZ

and try our compare products tool

Specifications are subject to change without notice * Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain