

COMMERCIAL



SUPER 104

AVAILABLE DECK SIZES

104" RD



SUPER 104

SmoothTrak™ Steering

Precision control to help trim and maneuver easily around obstacles. You will fully understand SmoothTrak™ steering when you drive ours

HyperDrive® Hydro System

Features industrial-grade pumps and motors to handle tough jobs and long days

Hydraulic Deck Height Adjustment

Raising and lowering your cutting height has never been easier

Hydraulic Wings

Easily raise and lower wings for transporting



Commercial-Grade

Kawasaki® FX1000 EFI engine

13M Suspension Seat

High-back seat with adjustable armrests and 3-inch suspension travel range

80" Transport Width

Fits most trailers making it easy to transport from job-to-job.

104" Width of Cut

Widest and most productive commercial zero-turn available

SUPER 104



- ✔ 104" Width of cut
Widest and most productive commercial zero-turn mower available
- ✔ 80" Transport width
Fits most trailers making it easy to transport from job-to-job
- ✔ HyperDrive® Hydro system
- ✔ Mows a football field in under 10mins

LIMITED WARRANTY
2 YEAR NO
YEAR HOUR LIMIT

OR

LIMITED WARRANTY
5 YEAR 500
YEAR HOUR



HYPERDRIVE SYSTEM

Increase the life and performance of your mower with Hustler's exclusive HyperDrive® system, the largest, most durable drive system in the industry. With temperature regulation and heavy-duty components, HyperDrive will keep you operating at peak performance.



9" fan & high capacity oil cooler with hot oil shuttle



Large oil reservoir



Heavy-duty Parker TG0360 wheel motors



Industrial grade slipper piston pumps

INDUSTRY'S
BEST WARRANTY

5 YEAR 3000
YEAR HOUR

**PUMPS
AND
MOTORS**

SUPER 104 ACCESSORIES

- ▶ Mulch kit
- ▶ Steering lever extension kit
- ▶ Anti-scalp kit
- ▶ FlexForks®
- ▶ Hitch kit
- ▶ Semi-pneumatic tyre 15x6 black

SUPER 104

ENGINE	
Manufacturer	Kawasaki® FX series
HP	38.5HP Kawasaki® FX1000 EFI (Per SAE J1995)
Displacement	999c
Cooling	Air cooled
Air Cleaner	Heavy duty canister
Engine Warranty	3 year
DRIVE SYSTEM	
Type	Dual hydrostatic
Pumps	Danfoss DDC-20
Wheel Motors	Parker TG0360
Hydraulic Lines	Stainless Parker Seal-Lok™ Technology
Reservoir Capacity	11.4L
Speed	Up to 18 kph
Parking Brakes	Patented automatic
DECKS	
Cutting Width	Rear discharge: 104"
Cutting Heights	1" - 5.5"
Deck Lift	Hydraulic powered
Depth	5.5"
Blades	5
Blade Length	1- 23.86" x 2.50" x 0.20 CW 1-23.86" x 2.50" x 0.20 CCW 1- 20.50" x 2.50" x 0.20 CCW 2-20.50" x 2.50" x 0.20" CW
Blade tip speed	Wing decks: 15,800 Center deck: 15,500
Spindles	Ductile cast iron with steel shaft and sealed ball bearings
Drive	Electric PTO Clutch
Construction	11 ga. welded steel
Spindle mounts	Reinforced 7 ga. doubler
Impact/Trim areas	1.5" x 0.375" steel bar
CONSTRUCTION	
Frame	1.5" x 3" steel tubing
Front Caster wheels	Mounted with tapered wheel bearings and debris cap
Front Caster forks	Fabricated 1/2" steel
GENERAL	
Seat	I3M suspension seat, adjustable arm rests and back support
Fuel Capacity	45.4 Litres
Cupholder	Yes
Front Tyre	13 x 6.5 - 6
Drive Tyre	26 x 12 - 12
Wing Tyre	11 x 4 semi-pneumatic
DIMENSIONS	
Weight	1134kg
Height w/rops up	1.82m
Height w/rops folded	1.37m
Length	2.43m
Width	2.69m wings down 2.03m wings up at gauge wheels 1.84m wings up at deck base
Tyre width	1.53m
Trim side	0.59m
PRODUCTIVITY*	
Acres Per Hour	9.24



VISIT HUSTLERMOWERS.CO.NZ
and try our compare products tool

Specifications are subject to change without notice

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain