



X-ONE

AVAILABLE DECK SIZES

54" & 60"



X-ONE



Fabricated Frame for Durability

1.5" x 3.0" steel frame making it one of the toughest and most durable in its class

NEW!

VX Deck

Fabricated 7 ga. steel engineered for extreme vacuum for enhanced performance and cut quality

Foot Operated Deck Lift

Easily adjust the deck height between 1" - 5.5" with less effort than hand-operated levers found on other brands

Commercial-Grade Torque

Parker unitized transmissions

SmoothTrak™ Steering

Precision control to help trim and maneuver easily around obstacles. You will fully understand SmoothTrak™ steering when you drive ours

Commercial-Grade Engine

Kawasaki® FX Engine options backed by 3 year warranty

I3M Suspension Seat

High-back seat with adjustable armrests and 3-inch suspension travel range





X-ONE

ACCESSORIES

- ▶ Semi pneumatic front tires
- ▶ Steering lever extension kit
- ▶ BacVac bagger (10 bushels)
- ▶ FlexForks®
- ▶ Mulch kit
- ▶ Electric deck kit
- ▶ Hitch kit

VX DECK TECHNOLOGY

Engineered
for extreme
vacuum

The all new Hustler VX deck more efficiently draws the grass up onto the mower blades providing a cleaner cut which in turn creates a superior after cut appearance



X-ONE

ENGINE	
Manufacturer	Kawasaki® FX series
HP	54", 60" decks: 27HP - FX850 (Per SAE J1995)
Displacement	FX850: 852cc
Cooling	Air cooled
Engine Warranty	3 year
DRIVE SYSTEM	
Type	Dual hydrostatic
Transmission	Parker unitized 12cc/rev pump & 15.9ci/rev wheel motors
Speed	Up to 17 kph
Parking Brakes	Patented automatic
DECKS	
Cutting Width	Side discharge: 54", 60"
Cutting Height	1.0" - 5.5"
Deck Lift	Foot operated
Depth	5.5"
Blades	3
Blade Length	54" deck: 18.3" 60" deck: 20.50"
Blade Tip Speed	54" deck: 17,700 60" deck: 18,800
Spindles	Ductile cast iron with steel shafts and sealed ball bearings
Drive	Electric PTO clutch
Construction	Fabricated 7 ga. with 7ga wrappers
Spindle Mounts	54", 60" deck: reinforced 7ga. stamped disc
Impact/Trim Areas	11ga. formed channel with rolled edge
CONSTRUCTION	
Frame	1.5" x 3.0" steel tubing
Front Axle	Fabricated with tapered roller bearings
Front Caster Wheels	Mounted with tapered greasable bearings and debris cap
Front Caster Forks	Fabricated 1/2" steel
GENERAL	
Seat	I3M suspension seat
Fuel Capacity	44.3 Litres
Cupholder	Yes
Front Tyre	13 x 6.5 - 6
Drive Tyre	54": 24 x 9.5 - 12 60": 24 x 12 - 12
DIMENSIONS	
Weight	54" deck: 562kg 60" deck: 565kg
Height	1.24m 1.84m w/ROPS up
Length	2.04m
Width w/Chute	54" deck: 1.38m 60" deck: 1.59m
Tyre width	54": 1.30m 60": 1.38m
Trim Side	54" deck: 0.04m 60" deck: 0.08m
PRODUCTIVITY*	
Acres per hour	54": 5.52 60": 6.36



VISIT HUSTLERMOWERS.CO.NZ
and try our compare products tool



OR



Specifications are subject to change without notice

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain